POWERHOLD™

Outdoor Carpet Adhesive

715

DESCRIPTION

POWERHOLD™ 715 Outdoor Carpet Adhesive is a “best-in-class” latex adhesive for exterior installations of indoor/outdoor carpet. POWERHOLD 715 bonds artificial turf and indoor/outdoor carpet in exterior installations only to concrete, asphalt paving and other clean, sound paving surfaces (not for use with asphalt roofing), exterior- or marine-grade plywood decking which is sound and not subject to deterioration (not for use with plank decking or treated wood), roughened aluminum boat decks, and abraded fiberglass. Substrates that have been painted, stained or otherwise coated must be tested to ensure compatibility with the adhesive.

USE FOR

Indoor/outdoor carpet and artificial turf in exterior installations only. Not for use with vinyl-backed or urethane-backed carpet. Not for use with asphalt roofing, plank decking or treated wood.

BONDS TO

Refer to the flooring manufacturer’s specific recommendations for suitable substrates.

Porous: Concrete, asphalt paving and other clean, sound, solid paving surfaces and cementitious underlayments. Untreated, exterior or marine-grade plywood decking.

- Please note that we cannot be responsible for failures resulting from deterioration of the plywood itself. Do not install over plank decking. Substrates that have been painted, stained, or otherwise coated must be tested to ensure compatibility with adhesive.

Non-porous: Abraded fiberglass substrates, roughened aluminum boat decks. Substrates that have been painted, stained, or otherwise coated must be tested to ensure compatibility with adhesive. Do not install over rubber or asphalt roofing.

PREPARATION

This adhesive is for outdoor use only.

Refer to the flooring manufacturer’s specific recommendations.

Acceptable installation temperatures range from 65°F (18°C) to 100°F (38°C).

Substrate must be sound, smooth and flat. Ensure that the substrate is solid and securely fixed to provide a rigid base free of undue flex. All loose substrates must be re-nailed or bonded properly to create a sound surface.

Substrate must be clean and dry. Mechanically remove dirt, wax, grease, oils, curing compounds and all foreign matter that would interfere with proper adhesion.

INSTALLATION

Adhesive is water resistant after five days. Protect from water for five days after installation.

Stir any liquid found on the surface into the adhesive, and full spread the adhesive using the proper trowel. A 100% transfer of adhesive into the carpet backing, while maintaining full coverage of the substrate, must be obtained.

Install carpet or turf immediately into wet adhesive. Do not allow a heavy film to form on surface of the adhesive. If the adhesive dries or skins over, it must be scraped up, and fresh adhesive needs to be applied. Cut, fit and reposition within 70 minutes. Working time will vary based on jobsite conditions, substrate, temperature and humidity. Lift a newly laid area occasionally to make sure adhesive is transfering fully to the back.

After installation, roll the flooring with a 100 lb. roller across width and length, as recommended by the flooring manufacturer. Stiff carpet should be re-rolled in 2 hours.

Cut and seal all seams as recommended by the carpet manufacturer.

CLEANUP

Remove wet adhesive residue with a clean, white cloth dampened with soapy water. Use mineral spirits for dried adhesive residue. When using mineral spirits, carefully follow the recommendations of the manufacturer, and test a small area before proceeding to make sure it does not damage the surface being cleaned.

WARRANTY

2-YEAR LIMITED, PRO-RATED WARRANTY. This limited warranty is your assurance that POWERHOLD 715 meets our high standard of quality and excellence. POWERHOLD 715 is warranted against cohesive failure (loss of bond) and formulated so as not to discolor or cause adhesive-induced staining in today’s floor coverings. This limited warranty covers flooring sold and graded as regulars, not seconds or trials.

POWERHOLD 715 is guaranteed for the life of the floor covering, up to two years, provided all manufacturers’ recommendations and industry standards, such as those set forth in ASTM F2170 and RFCI guidelines, are followed as they pertain to the type of floor covering being installed. Floor covering must be professionally installed.

This limited warranty covers materials* for the life of the installation, up to two years, and reasonable labor costs.

THIS LIMITED WARRANTY DOES NOT COVER: Dissatisfaction due to improper maintenance, installation or subfloor irregularities; topical staining; failures due to excessive moisture in substrates or flooding; mildew caused by patching compounds; installation or use of this adhesive over existing cutback adhesive or its residue; installation of residential flooring in a commercial application; or installation over sealers or curing agents.

CONSEQUENTIAL OR INCIDENTAL DAMAGES: Adhesive manufacturer excludes and will not pay consequential or incidental damages under this limited warranty. By this, we mean any loss, expense or damage other than to flooring itself that may result from a defect in the adhesive itself.

NO OTHER WARRANTIES: The above warranties are the only warranties offered by the adhesive manufacturer regarding POWERHOLD 715. Adhesive manufacturer specifically disclaims any other warranties, including the warranties of merchantability and fitness for a specific purpose, and there are no other warranties, expressed or implied. In the event of a warranty claim, adhesive manufacturer reserves the right to inspect and/or conduct test(s) on any claim prior to authorizing repair or replacement work.

*Materials meaning same type and grade, if available. If unavailable or discontinued, adhesive manufacturer reserves the right to pay dollar amount of initial amount on a pro-rated basis.

Failure to follow written directions will void the warranty.

Outdoor Carpet Adhesive

715

NOTES

- FOR PROFESSIONAL USE ONLY.
- Freeze/thaw stable to 10°F (-12°C). Avoid lower temperatures or multiple freeze/thaw cycles.
- Shelf life is 1 year, if unopened.
- VOC: 76 g/L, calculated, SCAQMD 1168

Do not reuse container. Dispose of container and residue in accordance with federal, state and local waste disposal regulations. Do not flush material down drains.

PRECAUTIONS

Carefully read and follow all precautions and warnings on the product label. For complete safety information, please refer to the Material Safety Data Sheet (MSDS) available at www.powerhold.net.

SIZES AVAILABLE:

4 Gallons (15.14 L)
1 Gallon (3.78 L)

TROWELS & COVERAGE

Recommended trowel sizes are guidelines only and are minimum requirements. Rough, porous concrete or asphalt paving and heavily textured carpet backings may require additional adhesive. A 100% transfer of adhesive into the carpet backing, while maintaining full coverage of the substrate, must be maintained.

U-Notch D=3/32", W=1/8", A=1/8"

Smooth-Back Carpet

108-126 sq. ft. / gal.
27-31.5 sq. ft. / qt.
2.5-3 sq. m / L

V-Notch D=1/8", W=1/8", A=1/16"

Rough-Back Carpet and All Installations on Rough Asphalt and on Extremely Porous or Rough Concrete

54-72 sq. ft./ gal.
17.5-20 sq. ft./ qt.
1.3-1.7 sq. m/ L

Made in the USA for:

FCDA / POWERHOLD

© 2013 FCDA / POWERHOLD. All rights reserved.
06-26-2013

FCDA / POWERHOLD
www.powerhold.net
FCDA
P.O. Box 7558
Fort Worth, TX 76111
(800) 232-4832 (Phone)